

STOIP 2450

ACRONI

ACRONI d.o.o., Cesta Borisa Kidriča 44, SI-4270 Jesenice

Izdajatelj/certifikata
Aussteller der Bescheinigung
Originator of the document

3.75

KONTROLA KAKOVOSTI
Telefon: +386 4 584 10 40
Telefax: +386 4 584 10 68
http://www.acroni.si
E-mail: miran.pirnat@acroni.si



Potrdilo o prevzemu 3.1/ Abnahmeprüfzeugnis 3.1/ Inspection certificate 3.1

Narocnik / Kunds / Customer

Stran/Seite/Page 1/2 EN 10 204 3.1
St./Nr./No Datum / Datum / Date

310061790-1 28.05.2013

Narocilo / Bestellung Nr. / Order No. Dobavni list / Lieferschein / Despatch note
55177-I disp 37094 **310061790 z/vom/from 27.05.2013**

Izdelek / Erzeugnis / Product Vrsta peči / Erschmelzungsart / Melting furnace Znak izvedenca TK Znak proizvajalca
Hot Rolled Annealed and Pickled **E+VOD** Zeichen des sachverständigen Zeichen des Herstellerwerks
Inspectors' stamp  Mark of the Manufacturer 

Specifikacije / Vorschriften / Specifications ASTM A240 Ed.2011 ASME SA240/240M, BPVC, Sec. II, Part A, Ed 10, Add 11a QQ-S-766D AMS 5507F/AMS 5524L EN 10028-7/ED.2008	Tip / W.nr. / Type 316L/316 316L/316 S31603/S31600 SAE 30316L/30316 X2CrNiMo 17/12/2 / 1D X5CrNiMo 17/12/2 W.Nr. 1.4404/1.4401	Pov / Fläche / Finish Koroz. test / Int.krist.korr. / Corrosion test No. 1 ASTM A262 PRACTICE E:OK No.:1
		EN ISO 3651-2 Method A:OK NACE MR 0103-2007 NACE MR 0175-2003

PED/97/23/EC

Obseg dobave / Umfang der Lieferung / Extent of material delivery

Poz. / Item	St. sarže / Schmelzen Nr. / Heat No.	St. plošče / Walztafel / Plate No.	Teža neto / Gewicht / Weight kg	Dimenzije / Abmessungen / Dimensions	St. kom. / Stückzahl / Quantity	St. vzorca / Probe Nr. / Sample No.
8	284586	78380	9203	3.75 / 78 / 240	1	78380 T

Mehanske lastnosti / Mechanische Eigenschaften / Mechanical properties

St. vzorca / Probe Nr. / Sample No.	Smer vzorca / Proben lage / Position	Nap.tecenja / Dehn / grenze 2% kSI	Nap.tecenja / Dehn / granza / Yield 1% kSI	Nat.trdnost / Zugfestigkeit / Tensile str. kSI	Raztezok / Bruchdehnung / Elongation / AS % / A50 % / A80 %	Kontrakt. / Einschnurung / g	Trdota / Harte / % / Hardness HR15C	Zilavost / Kerbschlag / Impact / pri / smer / bei / Lage / at / posit / °F
Zahteva / Anforderung	MIN	30	75	40			95	
	MAX							
78380 T	P	41,76	77,57	53.0	56.0	73	76	259 259 257 68

G - Glava / Kopf / Top N - Noga / Fuss / Bottom V - Vz dolžno / Langs / Longitudinal P - Precno / Quer / Transverse Upogib / Biege / Bend :

ACRONI
A. Pirnat
Cesta Borisa Kidriča 44, SI-4270 Jesenice
Tel: +386 4 584 10 40
Fax: +386 4 584 10 68
E-mail: miran.pirnat@acroni.si

19.02

(Signature)

1120