





92534

 <p><b>JSC DNEPROSPETSSTAL</b> YUZHNOYE SHOSSE 69008, ZAPOROZHYE UKRAINE</p> 	Purchase order No.: 07149 TECHN. PROTOCOL №У ДСС001-04 SPEC. № 8712/064776-CV Lot2 „AD 2000-Merkblatt WQ/TRD 100, 97/23/EG(DGRU)“ "DIN EN 10088-3, DIN EN 10272, ASTM A276-04, ASTM A479/A479M-04, ASME SA-479/SA-479M-04, ASTM A193/A193M-04c GR B8, CL 1D, ASME SA-193/SA-193M-04 GR B8, CL 1D, ASTM A182/A182M-05, ASME SA-182/SA-182M-04, AMS-QQ-S-763A-03 Cond.A, AMS 5639H-02, AMS 4647H-02, NACE MR 0175										Sheets: 8 Sheet:2 <b>QUALITY CERTIFICATE EN10204/3.1 Nr.199757</b> PLANT ORDER № 8071498712																																																																																				
	<b>PRODUCT DESCRIPTION</b> Rods of stainless steel, hot rolled, peeled. Прутки из нержавеющей стали горячекатаные, обточенные. <b>STEEL MAKING PROCESS:</b> Electric furnace <b>СПОСОБ ВЫПЛАВКИ:</b> Электрическая дуговая печь Round 158.75 mm L=3,8-5,8m 6 1/4" Grade: 304L/1.4307										QUANTITY: 1bundQ-1540kg (number of pcs) 1 Q-860kg  Delivery condition Heat-treated (solution annealing 1000°-1080° water) С термич.обработ. (закалка в воду 1000°-1080°)																																																																																				
CUSTOMER: „DSS International SA“ Switzerland "DIN EN 10088-3, DIN EN 10272, ASTM A 276, ASTM A 479"																																																																																															
<table border="1"> <thead> <tr> <th>ANALYSES, %</th> <th>C</th> <th>Si</th> <th>Mn</th> <th>P</th> <th>S</th> <th>Cr</th> <th>Ni</th> <th>Mo</th> <th>Al</th> <th>Cu</th> <th>V</th> <th>W</th> <th>Ti</th> <th>Co</th> <th>Nb</th> <th>N<sub>2</sub></th> <th>Sn</th> <th>B</th> </tr> </thead> <tbody> <tr> <td>REQUIRED</td> <td>&lt;.030</td> <td>&lt;.1,0</td> <td>&lt;.00</td> <td>&lt;.045</td> <td>&lt;.030</td> <td>18.00-19.50</td> <td>8.0-10.0</td> <td>&lt;.30</td> <td>&lt;.10</td> <td>&lt;.40</td> <td>&lt;.10</td> <td>&lt;.20</td> <td>&lt;.15</td> <td>&lt;.40</td> <td>&lt;.20</td> <td>&lt;.10</td> <td></td> <td></td> </tr> <tr> <td>CAST № 92534</td> <td>.022</td> <td>.28</td> <td>1.57</td> <td>.033</td> <td>.027</td> <td>18.41</td> <td>8.12</td> <td>.25</td> <td>.064</td> <td>.28</td> <td>.03</td> <td>.07</td> <td>.006</td> <td>.059</td> <td>.01</td> <td>.077</td> <td>.011</td> <td>.0014</td> </tr> </tbody> </table>																		ANALYSES, %	C	Si	Mn	P	S	Cr	Ni	Mo	Al	Cu	V	W	Ti	Co	Nb	N <sub>2</sub>	Sn	B	REQUIRED	<.030	<.1,0	<.00	<.045	<.030	18.00-19.50	8.0-10.0	<.30	<.10	<.40	<.10	<.20	<.15	<.40	<.20	<.10			CAST № 92534	.022	.28	1.57	.033	.027	18.41	8.12	.25	.064	.28	.03	.07	.006	.059	.01	.077	.011	.0014																					
ANALYSES, %	C	Si	Mn	P	S	Cr	Ni	Mo	Al	Cu	V	W	Ti	Co	Nb	N <sub>2</sub>	Sn	B																																																																													
REQUIRED	<.030	<.1,0	<.00	<.045	<.030	18.00-19.50	8.0-10.0	<.30	<.10	<.40	<.10	<.20	<.15	<.40	<.20	<.10																																																																															
CAST № 92534	.022	.28	1.57	.033	.027	18.41	8.12	.25	.064	.28	.03	.07	.006	.059	.01	.077	.011	.0014																																																																													
<table border="1"> <thead> <tr> <th rowspan="2">MECANICAL PROPERTIES</th> <th colspan="2">Yield Strength,</th> <th rowspan="2">Tensile Strength, Rm N/mm<sup>2</sup></th> <th colspan="2">Elongati on A<sub>5</sub> %</th> <th colspan="2">Reduction of area, Z %</th> <th rowspan="2">Brinell Hardness HB</th> <th colspan="3">Impact strength, KV, J</th> <th colspan="8">TECHNICAL REQUIREMENTS:</th> </tr> <tr> <th>N/mm<sup>2</sup> R0.2%</th> <th>R1.0%</th> <th>L</th> <th>Q</th> <th>L</th> <th>Q</th> <th>1</th> <th>2</th> <th>3</th> <th>1</th> <th>2</th> <th>3</th> <th colspan="8">           Macrostructure – GOOD            GRAIN SIZE: 5 to ASTM E 112            Nonmetallic inclusions ASTM E 45-95 (Method A)            A B C D            thin thick thin thick thin thick thin thick            2.5 2.0 1.5 1.0 0 0 1.0 1.0            ICC-DIN 50914 (EN 114, EN ISO 3651-2)-test: O.K.            „Anti-mixing test – O.K.“            “Dimension test and surface defects test is accomplished”         </th> </tr> </thead> <tbody> <tr> <td>REQUIRED</td> <td>205</td> <td>230</td> <td>515-680</td> <td>45</td> <td>50</td> <td>Max215</td> <td>100</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>EFFECTIVE</td> <td>397</td> <td>405</td> <td>611</td> <td>59</td> <td>76</td> <td>179</td> <td>267</td> <td>269</td> <td>272</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> </tbody> </table>																		MECANICAL PROPERTIES	Yield Strength,		Tensile Strength, Rm N/mm <sup>2</sup>	Elongati on A <sub>5</sub> %		Reduction of area, Z %		Brinell Hardness HB	Impact strength, KV, J			TECHNICAL REQUIREMENTS:								N/mm <sup>2</sup> R0.2%	R1.0%	L	Q	L	Q	1	2	3	1	2	3	Macrostructure – GOOD GRAIN SIZE: 5 to ASTM E 112 Nonmetallic inclusions ASTM E 45-95 (Method A) A B C D thin thick thin thick thin thick thin thick 2.5 2.0 1.5 1.0 0 0 1.0 1.0 ICC-DIN 50914 (EN 114, EN ISO 3651-2)-test: O.K. „Anti-mixing test – O.K.“ “Dimension test and surface defects test is accomplished”								REQUIRED	205	230	515-680	45	50	Max215	100												EFFECTIVE	397	405	611	59	76	179	267	269	272									
MECANICAL PROPERTIES	Yield Strength,		Tensile Strength, Rm N/mm <sup>2</sup>	Elongati on A <sub>5</sub> %		Reduction of area, Z %		Brinell Hardness HB	Impact strength, KV, J			TECHNICAL REQUIREMENTS:																																																																																			
	N/mm <sup>2</sup> R0.2%	R1.0%		L	Q	L	Q		1	2	3	1	2	3	Macrostructure – GOOD GRAIN SIZE: 5 to ASTM E 112 Nonmetallic inclusions ASTM E 45-95 (Method A) A B C D thin thick thin thick thin thick thin thick 2.5 2.0 1.5 1.0 0 0 1.0 1.0 ICC-DIN 50914 (EN 114, EN ISO 3651-2)-test: O.K. „Anti-mixing test – O.K.“ “Dimension test and surface defects test is accomplished”																																																																																
REQUIRED	205	230	515-680	45	50	Max215	100																																																																																								
EFFECTIVE	397	405	611	59	76	179	267	269	272																																																																																						
Heat treatment (specimen) Delivery condition: In state of delivery																																																																																															
US - testing yes Results: SEP 1921, 3/ Dd O.K.																																																																																															
Radiation free; mercury free. No Weld or Weld repair.																																																																																															
Manufacturer: JSC DNEPROSPETSSTAL Date: 09.08.07 Signed:  Zaporozhye Made in Ukraine.																																																																																															



60464