S. A. A. TE PRODUCT

CANADA

DEOW

REPORT OF CHEMICAL/PHYSICAL TESTS

E

256461

MILL ORDER NO.

1255606

Aug

30, DATE

2012

PAGE

CERTIFICATE NO. DATE

CUSTOMER ORDER NO.

P20720CT001E

SHIPPING NO.

08/30/2012

JOB/REQ. NO.

ATTN: CATHY STEPANIUK WILKINSON STEEL & METALS INC [EDMN] EDMONTON, AB 9525 60 AVE T6E 0C3 EDMONTON, AB 9525 60 AVE WILKINSON STEEL AND METALS INC -CANADA T6E 0C3

THIS MATERIAL HAS BEEN MANUFACTURED, TESTED AND FOUND TO MEET THE SPECIFICATIONS AND PURCHASE ORDER REQUIREMENTS CARRIER 1255606

	PHYSICAL PROPERTIES	
	Children Commence of the Comme	CALL
MILTE	TAITTY KILLED FINE GRAIN PRACTICE. LCVN 20 FT.LBF AVG @ -50 F (continued)	T.TAT.
	010/11A ADD. NORMALIABU FER NACE MEET OF SELECTION	/OTC
CAH/IRUCK NO.	10 /11 TOWN TERM OF WEOLTS WELL DEPOSITE DESCRIPE VESSEL	1
	CANDON TABLECARE VESCEE MORELLE AND THE CONTROL OF COMMENT	000
ONTON PACTETO	OG GRADE 70 ASME SAS16 GRADE 70	מ
THIT ON THE C		S SALVIES A

								_			-		.,	_	T	a				-
HEAT													υ 	-	3	ONWELL		QUAL	201	
NO					н				н			SCHE	000	H				QUALITY.	2010/11A	1111
HEAT NO. C				1 P	THE FOLLOWING PLATES WERE			1 Þ	THE F			SCHEDULE B:7208.52.00	1.0000 X 96.000ME X 480.000	F.	1					
Mn				PC	OLLO			PC	FOLLOWING			B:7	96.0	t	THE MIN			ILLE	U. N	1
S)				13	MING			130	MINC			208	OOME	. AT T. L.	NTN	DESC		DFI	ORMA	1777
P				13068 LBS	3 PL			13068	3 PL			52.	×		١	DESCRIPTION		NE	PTZI	- + 71
1				LBS	ATES			LBS	ATES			00	180.	0	M OOC	S S		KILLED FINE GRAIN PRACTICE.	בין	;
S				Н	WER			1	WER				000		MAX RHU			N PR	EK NA	IN CL
Si				2H09	NO			2H09	E NO									ACTI	1 TO	1
5				12H0998 ^	NORMALIZED			12н0999 ^	PLATES WERE NORMALIZED AT		>				(P)			E.	TROL	LOGN
				NW6236	IZED			NW6236	IZED		NW6236					HEA		LCV.	N D	JE N
Z.				236	AT			236			236					HEAT NO.		N 20	N E	LIM (
٧	CH		A28	A27	1660		A27	A26	1660		A26					SLAB	PHYSICAL PROPERTIES	LCVN 20 FT. LBF AVG @ -50 F	ADD. NORMALIZED FER NACE MROI/S NO WELL SEFEIX.	7 0 0 1
СЬ	CHEMICAL ANALYSIS		ر ا		DEGS		б		SPEC		ر ت		-			YIELD TENSILE PSI X 100 PSI X 100	SICA	BF A	1 2 1 1	STAG
≥	SAL	F	520		দ	H	515		ㅂ	r	520				-	00 PS	L	(G)	1	
_	ANA	LCVN @ -50	760		FOR 45	LCVN	765 30		OR 4	LCVN	760						OP	-50	1 0	DRESSIRE VESSEL
δ	LYS	(8)	760 33			® -50	30		5 M	® -50	32					% ELONG 8" 2"	H	72	1	IRE
Mo	S	0 DEG			NUTE			-	NUTE	-	_	_	_				S	(00)	1 0	TESSI
=		G Ħ			S AN	DEG F			S AN	EG F						% RA		(continued)		ä
		10.0mm		159	MINUTES AND AIR	10.0mm		156	FOR 45 MINUTES AND AIR	10.0mm						HARDNE		red)	- D	
8		mm		9			_	6								HARDNESS BEND BHN TEST				
z		110			COOLED	108	-		COOLED	90 1						48				
		159			J	112				21 1										
Ca		115				98 /				/ 80								1	HW	CAH/ HUGA NO.
		/ 12				98 / 106.0				90 121 108 / 106.3						7			WHITE	CA NO.
+		128.0				.0										IMPACTS				
		Hi (†				ft.lbf				ft.lbf						S				
C	2	ft.1bf				T d				H										
Grain Size	-																			
9	3						_			_	_			-		1			_	

I certify the above to be correct as contained in the records of EVRAZ INC. NA

Ву

NW6236

HEATS INDICATED WITH (+) WERE MELTED & MANUFACTURED IN THE USA. HEATS INDICATED WITH (^) WERE ROLIED IN THE

HEAT NO.

. 20

1.33 M

.011

.005

.33 Si

. 02

. 05 Z

.027

.005 S

.033

.02 Q

.00 S

.002

.0000 8

USA.

Richard Deschand Quality Coordinator

REPORT OF CHEMICAL/PHYSICAL TESTS

S. A. ATE PRODUCES

9525 60 AVE ATTN: CATHY STEPANIUK WILKINSON STEEL & METALS EDMONTON, AB CANADA T6E 0C3 INC [EDMN]

> WILKINSON STEEL AND METALS INC -CANADA EDMONTON, AB 9525 60 AVE T6E 0C3

CUSTOMER ORDER NO. JOB/REQ. NO. 256461 P20720CT001E

SHIPPING NO.

뛉

MILL ORDER NO.

1255606

30, DATE

2012

CERTIFICATE NO.

DATE Aug

CAR/TRUCK NO. CARRIER 1255606 UNION PACIFIC 08/30/2012

THIS MATERIAL HAS BEEN MANUFACTURED, TESTED AND FOUND TO MEET THE SPECIFICATIONS AND PURCHASE ORDER REQUIREMENTS 2010/11A ADD. NORMALIZED PER NACE MR0175 NO WELD REPAIR. EOS CARBON PRESSURE VESSEL QUALITY ASTM A516-06 GRADE 70 ASME SA516 GRADE 70 KILLED FINE GRAIN PRACTICE. LCVN 20 FT.LBF AVG @ -50 F PRESSURE VESSEL (continued)

QUALITY. WHITE

	×									77.75	(u	ONMEIL	
н	NW6236	HEAT NO.										- 0	NO	
HEATS		Ō				4	1	THE		Р	THE) 16 FT.		
INDE	1	C				PCS	PC			PC	FOL	T.LBI		
INDICATED	1.33	M				ì	<u>1</u>	FOLLOWING		13	COWIN	FT.LBF MIN.	DES	
O WITH (+) WERE	.011	ס				52272 LBS	13068 LBS	G PLATES		13068 LBS	P] ;	×	DESCRIPTION	
(+)	.005	S				S TO	ŭ			ល	ES WE	200 MAX BHN 480,000	_	
	33	Si				TOTALS	12H0	WERE NO		12H09	RE NO			
MELTED	.02	<u>0</u>				ANGES STATE	12H0996 ^	NORMAL I ZED	<i>0</i> 4.	12H0997 ^	DRMAL	(P).		
R)	. 05	Z.					NW6236	ZED AT		NW6236	NORMALIZED AT		HEAT NO.	STATE OF
MANUFACTURED	.027	<	악				A29	1660	A29	A28	1660). SLAB	РНҮ
	.005	Cb	CHEMICAL ANALYSIS					DEGS F	530		F SPEC		YIELD PSI:X 100	PHYSICAL PROPERTIES
IN THE	.033	A	AL AN						LO		FOR 45		TENSILE PSI X 100	PRO
USA.	.02	Cr	JALYS						(B) (N)				E % ELONG 00 8" 2"	PERT
HEATS	.00	Mo	SIS					MINUTES	-50 DEG		MINUTES			IES
	.002	=1							'Tj		S AND		%RA	
INDICATED	2 .0000						131	AND AIR COOLED	10.0mm	157	AIR		HARDNESS BEND BHN TEST	
	00			_				00					S BEN	
HTIW		z						CED	71 115		COOLED	520	10	
WITH (^) WERE ROLLED IN THE		Ca							5 117					
VERI		H												
ROL									/ 101.0				IMP	
ED													IMPACTS	
N									ft.lbf					
THE		C							H					- Stores
USA.		Grain Size	-		etti — tip— E—									

Ву

END

OF REPORT